

G-SERIES PTFE FLANGED VALVE



Griffco G-Series diaphragm back pressure valves are designed to enhance the performance of chemical feed systems by applying a continuous back pressure to the chemical feed pump, while also acting as an anti-syphon valve. Robust construction ensures reliability in the rigorous service of sulphuric acid for both municipal and industrial applications. Wetted materials are: **PTFE**. Available sizes: DN15 – DN25.

Features:

- One Piece Machined Construction
- High Reliability / Low Cost
- Composite PTFE/EPDM Diaphragm
- Adjustable 1 - 10 Bar
- Optional PSI Rated Valves
- Anti-Syphon Function
- Bottom Support Disc
- Tamper Resistant Adjustment Screw
- Molded Noryl Top

Operation:

Griffco diaphragm back pressure valves apply positive discharge pressure to a metering pump system to prevent siphoning and eliminate varying dosage rates caused by fluctuating downstream pressure. The diaphragm is held against the valve seat by an internal spring. When the preset pressure is exceeded, the diaphragm is forced up and chemical flows through the valve to the injection point. The valves are preset for 3,5 bar, however they are field adjustable from 1 – 10 bar via the adjustment screw. Installation should be as close to the injection point as possible to prevent chemical line drainage, and it is most important that all chemical system equipment such as pulsation dampeners and pressure gauges are between the pump and back pressure valve.

TYPICAL INSTALLATION



